

LOWER PRESSURE HOSE

HOSE CONSTRUCTION

Tube made of synthetic rubber
Braided galvanized steel wire

SUITABLE FOR

Diesel Fuel
Hydraulic Fluid
Up to 80 deg centigrade



I/D	Operating Pressure / bar	Burst Pressure / bar	Test Pressure / bar	Part Number
4mm I.D.	20	60	30	S601304
6mm I.D.	15	50	25	S601306
8mm I.D.	15	50	25	S601308
10mm I.D.	15	5	25	S601310

LOWER PRESSURE HOSE

HOSE CONSTRUCTION

Tube made of textile braided hose made of
Synthetic vulcanized rubber

SUITABLE FOR

Diesel Fuel
Up to 80 deg centigrade



I/D	Operating Pressure / bar	Burst Pressure / bar	Test Pressure / bar	Part Number
5.5mm	10	30	20	S601504
7.5mm	10	30	20	S601506
11.0mm	10	30	20	S601510
3.0mm	LEAK-OFF HOSE			S603500
3.2mm	LEAK-OFF HOSE			S601550
4.5mm	LEAK-OFF HOSE			S603502

PVC HOSE

HOSE CONSTRUCTION

Synthetic fiber reinforcement between a
Soft PVC inner and outer tube

SUITABLE FOR

Diesel Fuel
Oil



I/D	O/D	PART NUMBER
4.0mm	10.0mm	S603102
6.0mm	12.0mm	S603104
8.0mm	14.0mm	S603106

POLYAMID PLASTIC PIPE

HOSE CONSTRUCTION

Plastic extruded pipe

SUITABLE FOR

Air Brake Line



O/D	Wall Thickness	Operating pressure (Bar) at 20 deg Centigrade	Part Number
4mm	1.0mm	45	S672018
6mm	1.0mm	27	S672001
8mm	1.0mm	19	S672003
11mm	1.5mm	21	S672010